

AMENDMENTS TO THE CLAIMS

The following is a complete listing of the claims, which replace all previous versions and listings of the claims.

1. (original) A computer system, comprising:

a chassis;

a processor;

a hard drive securing mechanism, the hard drive securing mechanism
being operable to secure a plurality of hard drives to the chassis
with a rotatable lever; and

at least one hard drive secured by the hard drive securing mechanism.

2. (original) The system as recited in claim 1, wherein each hard drive includes a plurality of protruding members, further wherein the hard drive securing mechanism is operable to secure the plurality of hard drives by restricting the movement of the plurality of protruding members.

3. (currently amended) The system as recited in claim 1, the hard drive securing mechanism further comprising:

a plurality of guides secured to the chassis to restrict the movement of a
~~the~~ plurality of protruding members; and

a hard drive carrier,

wherein the rotatable lever includes a plurality of tapered guides, each
tapered guide being configured to receive and secure a protruding
member.

4. (original) The system as recited in claim 2, wherein a first hard drive is securable between the lever and a first set of guides.

5. (currently amended) The system as recited in claim 3, wherein each tapered guide is configured to receive ~~[[a]]~~the protruding member when the rotatable lever is in a first position, further wherein, each tapered guide is configured to prevent movement of ~~[[a]]~~the protruding member when the lever is in a second position.

6. (original) The system as recited in claim 5, wherein the rotatable lever includes a protrusion biased by a flexible member, further wherein the protrusion is captured when the securing lever is disposed in the second position.

7. (currently amended) The system as recited in claim ~~[[3]]~~4, wherein a second hard drive is securable between the hard drive carrier and a second set of guides.

8. (currently amended) The system as recited in claim ~~[[3]]~~7, wherein the rotatable lever is operable to drive the carrier towards the second set of guides.

9. (original) The system as recited in claim 8, wherein the rotatable lever comprises a cam configured for sliding engagement with the carrier.

10. (original) The system as recited in claim 9, further comprising a spring, wherein the spring is compressed as the rotatable lever is rotated in a first direction, further wherein the spring biases the carrier towards the rotatable lever when the rotatable lever is rotated in a second direction.

11. (original) The system as recited in claim 3, wherein the rotatable lever comprises a tab for operating the rotatable lever.

12. (currently amended) The system as recited in claim ~~[[5]]~~10, wherein the rotatable lever comprises a stop that engages a surface on the carrier to prevent rotation of

the rotatable lever past the first position as the rotatable lever is rotated in the second direction.

13. (original) The system as recited in claim 12, comprising a moveable obstruction disposable over the rotatable lever, wherein when the moveable obstruction is disposed over the rotatable lever, the moveable obstruction prevents the rotatable lever from rotating from the second position to the first position, and further wherein, when the rotatable lever is disposed in the first position, the rotatable lever prevents the moveable obstruction from being disposed over the rotatable lever.

14. (currently amended) A hard drive securing system, comprising:
a plurality of guides secured to a chassis;
a hard drive carrier held by a first plurality of guides and configured to support a ~~computer~~ plurality of hard drives; and
a securing lever mechanism operable to secure the plurality of hard drives to the hard drive carrier.

15. (original) The system as recited in claim 14, wherein the securing lever mechanism has a guide portion configured to receive a portion of a hard drive when the securing lever mechanism is in a first position.

16. (original) The system as recited in claim 15, wherein a first hard drive is secured when the securing lever mechanism is rotated to a second position.

17. (original) The system as recited in claim 16, wherein the securing lever mechanism is operable to rotate from the first position to the second position.

18. (currently amended) The system as recited in claim 17, wherein the securing lever mechanism comprises a latch to secure the securing lever mechanism when the securing lever mechanism is in the second position.

19. (currently amended) The system as recited in claim 18, wherein the securing lever mechanism is configured with a cam to drive the hard drive carrier as the securing lever mechanism is rotated from the first position to the second position.

20. (original) The system as recited in claim 19, comprising a spring, wherein the spring opposes movement of the hard drive carrier produced by the securing lever mechanism and drives the carrier as the securing lever mechanism is rotated from the second position to the second position.

21. (original) The system as recited in claim 20, wherein the hard drive carrier is configured to secure a second hard drive against a second plurality of guides when the securing lever mechanism is in the second position.

22. (original) A method of securing a plurality of hard drives to a computer chassis, comprising:

disposing a first hard drive between a first restraint and a securing lever;
deploying a second hard drive between a second restraint and a carrier
configured to direct the movement of the second hard drive; and
rotating the securing lever to simultaneously secure the first hard drive by
the first restraint and the lever and the second hard drive by the
carrier and the second restraint.

23. (original) The method as recited in claim 22, further comprising:
providing each hard drive with a plurality of protruding members.

24. (original) The method as recited in claim 23, further comprising:
configuring the securing lever with a tapered guide to receive a first plurality of protruding members in a first position of the securing lever and to restrict movement of the first plurality of protruding members in a second position of the securing lever.
25. (original) The method as recited in claim 22, further comprising:
configuring the securing lever with a cam surface to drive the carrier in a first direction as the securing lever is rotated from a first position to a second position.
26. (original) The method as recited in claim 25, further comprising:
providing the chassis with a spring mechanism configured to oppose the movement of the carrier by the securing lever; and
using the spring mechanism to bias the carrier against the securing lever as the securing lever is rotated from the second position to the first position.
27. (original) The method as recited in claim 22, further comprising:
forming the restraints by cutting and bending a portion of the chassis to form a plurality of tabs, each tab configured to restrict the movement of a protruding member.
28. (original) A rotatable lever for securing a hard drive, having a plurality of protruding members, to a chassis, comprising:
a plurality of guides, each guide being configured to receive a protruding member when the securing lever is in a first position and to restrict the protruding member when the securing lever is in a second position.

29. (original) The rotatable lever as recited in claim 28, further comprising:
a first portion including at least one of the plurality of guides;
a second portion including at least a second of the plurality of guides and
an operator; and
a connector, connecting the first and second portions.
30. (original) The rotatable lever as recited in claim 29, wherein the first portion
and second portion include a cam surface.
31. (original) The rotatable lever as recited in claim 30, wherein each guide is
tapered.